SEAT SOFT 02.112.1 ZANO STREET FURNITURE







## **OPTIONS**

### **Construction:**

- o carbon steel (s235Jr)
- stainless steel (Aisi 304)

### Seat:

- o soft wood
- hardwood of European origin
- hard wood (oil finish)
- o premium hard wood

## Methods of installation:


- free-standing
- attached by bolts to foundation


### DESCRIPTION


Soft seat is a one-person chair with **armrests** and **no backrest**. It is fixed by rawlbolts to a hard surface (stone, concrete). It meets the requirements of furniture **adapted for use by the elderly**. Horizontal seat and high armrests facilitate standing up and sitting by elderly people and people with motor difficulties.

The armchair is available in several colour and material versions. The cheaper version is made of carbon steel, galvanized and powder coated in any RAL colour, while the seat of the furniture is made of lacquered spruce or pine furniture. In the more expensive version of the furniture we use stainless steel and exotic oiled wood (to choose: sapela, iroko, meranti). This combination of materials gives us a very elegant visual effect, while affecting the strength of the furniture and its resistance to external conditions. Using stainless steel and exotic wood, the furniture will retain its original, initial appearance for longer. Also its maintenance and cleaning is easier.

SEAT SOFT 02.112.1 ZANO STREET FURNITURE







# **GENERAL TECHNICAL DATA**

### **Dimensions:**

- width: 59 cm - length: 66 cm

- seat height: 47 cm

- height of armrests: 69 cm

### Materials:

- wood: European coniferous or exotic

- steel: carbon or stainless

# ZANO



Product: Seat Soft
Catalog number: 02.112.1

Twoma Zacust Designer: Iwona Zaczek

In accordance with the Polish Law on Copyright and Related Rights of 04.02.1994 (Official Journal of Laws No. 24, item 83, corrected: Journal of Laws No. 43, item 170) and in accordance with the EU copyright legislation including all EU directives and regulations on copyright, Zano Mirosław Zarotynski Company, reserves the copyright of drawings, descriptions, 3D models, renderings, graphics, content contained in offers, attachments to offers and all other documents. Its content is the intellectual property of ZANO Miroslaw Zarotinski company. The use of author's ideas, solutions, copying, distribution of photos, graphics or fragments of graphics, descriptive texts, for profit, without the permission of the author - ZANO Mirosław Zarotynski company - is prohibited and constitutes a copyright infringement and is punishable.

NOTE: The drawings do not reflect the actual dimensions of the foundation. They are only exemplary assembly schemes taking into account the type of anchoring and the substrate material to which the furniture is to be fixed.

The size of the foundation depends on the local foundation conditions.









# INSTALLATION INTO PAVING WITH FOUNDATION

### Description of the assembly

- 1. ZANO product
- 2. Quick-action fastener or chemical anchor
- 3. Stone paving / concrete paving / stone slabs / concrete slabs
- 4. Sand ballast (approx. 2 4 cm)
- 5. Stone aggregate substructure
- Concrete foundation, class C16/20 (top surface concrete 10 cm below paving surface)
- **7.** Ground

## **INSTALLATION TO PAVING**

### Description of the assembly

- 1. ZANO product
- 2. Quick-action fastener or chemical anchor
- 3. Stone paving / concrete paving / stone slabs / concrete slabs
- **4.** Sand ballast (approx. 2 4 cm)
- 5. Stone aggregate substructure
- 6. Ground

# CONCRETE / ASPHALT MOUNTING

#### Description of the assembly

- 1. ZANO product
- 2. Quick-action fastener or chemical anchor
- **3.** Fixed hardened surface e.g. concrete or asphalt
- Concrete foundation, class C16/20 (top surface concrete 10 cm below paving surface)
- **5.** Stone aggregate substructure
- 6. Sand ballast (approx. 2 4 cm)
- **7.** Ground

# MOUNTING TO CONCRETE FOUNDATION

#### Description of the assembly

- 1. ZANO product
- 2. Quick-action fastener or chemical anchor
- 3. Concrete foundation, class C16/20 (top surface concrete 10 cm below paving surface)
- 4. Ground