

OPTIONS

Construction:

- carbon steel (s235Jr)
- stainless steel (Aisi 304)

Decoration:


- soft wood
- hardwood of European origin
- hard wood (oil finish)
- premium hard wood

Methods of installation:

- free-standing
- attached by bolts to foundation

DESCRIPTION

The line of planters Block is a wide range of sizes in which everyone will find something for themselves. It's you, who decide in what type of steel and wood the construction will be made of. It has an universal shape that can goes well with diferent types of indoor and outdoor spaces.



GENERAL TECHNICAL DATA

Dimensions: - width: 77 cm

- height: 69 cm - depth: 77 cm

Weight: - 62 kg

ZANO

In accordance with the Polish Law on Copyright and Related Rights of 04.02.1994 (Official Journal of Laws No. 24, item 83, corrected: Journal of Laws No. 43, item 170) and in accordance with the EU copyright legislation including all EU directives and regulations on copyright, Zano Mirosław Zarotynski Company, reserves the copyright of drawings, descriptions, 3D models, renderings, graphics, content contained in offers, attachments to offers and all other documents. Its content is the intellectual property of ZANO Miroslaw Zarotinski company. The use of author's ideas, solutions, copying, distribution of photos, graphics or fragments of graphics, descriptive texts, for profit, without the permission of the author - ZANO Mirosław Zarotynski company - is prohibited and constitutes a copyright infringement and is punishable.

5





SINCE 198

wartości podane są w centymetrach

2/3

MOUNTING DIAGRAMS (A, B, C, D) FOR SCREW MOUNTING

NOTE: The drawings do not reflect the actual dimensions of the foundation. They are only exemplary assembly schemes taking into account the type of anchoring and the substrate material to which the furniture is to be fixed.

The size of the foundation depends on the local foundation conditions.









INSTALLATION INTO PAVING WITH FOUNDATION

Description of the assembly

- 1. ZANO product
- 2. Quick-action fastener or chemical anchor
- 3. Stone paving / concrete paving / stone slabs / concrete slabs
- 4. Sand ballast (approx. 2 4 cm)
- 5. Stone aggregate substructure
- **6.** Concrete foundation, class C16/20 (top surface concrete 10 cm below paving surface)
- 7. Ground

INSTALLATION TO PAVING

Description of the assembly

- 1. ZANO product
- 2. Quick-action fastener or chemical anchor
- **3.** Stone paving / concrete paving / stone slabs / concrete slabs
- 4. Sand ballast (approx. 2 4 cm)
- 5. Stone aggregate substructure
- 6. Ground

CONCRETE / ASPHALT MOUNTING

Description of the assembly

- 1. ZANO product
- 2. Quick-action fastener or chemical anchor
- **3.** Fixed hardened surface e.g. concrete or asphalt
- Concrete foundation, class C16/20 (top surface concrete 10 cm below paving surface)
- 5. Stone aggregate substructure
- 6. Sand ballast (approx. 2 4 cm)
- 7. Ground

MOUNTING TO CONCRETE FOUNDATION

Description of the assembly

- 1. ZANO product
- 2. Quick-action fastener or chemical anchor
- **3.** Concrete foundation, class C16/20 (top surface concrete 10 cm below paving surface)
- 4. Ground