OPTIONS

Construction:
- carbon steel (s235Jr)
- stainless steel (Aisi 304)

Seat and backrest:
- European coniferous wood
- hardwood of European origin
- oiled exotic wood
- premium exotic wood

Mounting method:
- to screw

DESCRIPTION

The Flash swivel lounger is our offering for enhancing spaces such as squares, parks, or waterfront green areas. Its swivel base allows users to easily rotate towards the sun. The Flash lounger is a contemporary style bench from our popular Flash series, known for its ample wooden slats and remarkable craftsmanship. Constructed from either stainless steel or black steel, and premium wood types like spruce, pine, or upon request, exotic woods, it's secured firmly to the ground with anchors.

GENERAL TECHNICAL DATA

Dimensions:
- width: 26 in
- length: 59 ³/₄ in
- height: 34 ¹/₄ in

Weight:
- 174 lb

Materials:
- wood
- stainless or carbon steel

ZANO

Product:
Flash swivel lounger
Catalog number: **02.525.1**
Designer: Filip Babiarz

NOTE: The drawings do not reflect the actual dimensions of the foundation. These are only sample installation diagrams taking into account the type of anchoring and the material of the substrate to which to attach the furniture.

The size of the foundation depends on local foundation conditions.

INSTALLATION TO PAVING WITH FOUNDATION

Installation description

1. ZANO product
2. Quick-attachment / quick-attachment or chemical anchor
3. Stone paving / concrete paving / stone slabs / concrete slabs
4. Sand ballast (approximately 2 - 4 cm)
5. Stone aggregate substructure
6. Concrete foundation of C16/20 class (top surface of concrete 10 cm below paving surface)
7. Local land

MOUNTING TO PAVING

Installation description

1. ZANO product
2. Quick-attachment / quick-attachment or chemical anchor
3. Stone paving / concrete paving / stone slabs / concrete slabs
4. Sand ballast (approximately 2 - 4 cm)
5. Stone aggregate substructure
6. Local land

MOUNTING TO CONCRETE / ASPHALT

Installation description

1. ZANO product
2. Quick-attachment / quick-attachment or chemical anchor
3. Fixed restrained surface, such as concrete or asphalt
4. Concrete foundation of C16/20 class (top surface of concrete 10 cm below paving surface)
5. Stone aggregate substructure
6. Sand ballast (approximately 2 - 4 cm)
7. Local land

MOUNTING TO CONCRETE FOUNDATION

Installation description

1. ZANO product
2. Quick-attachment / quick-attachment or chemical anchor
3. Concrete foundation of C16/20 class (top surface of concrete 10 cm below paving surface)
4. Local land