SEAT SOFT 02.112.1 ZANO URBAN FURNITURE





OPTIONS

Construction:

- o carbon steel (s235Jr)
- stainless steel (Aisi 304)

Seat:

- European coniferous wood
- hardwood of European origin
- oiled exotic wood
- o premium exotic wood

Mounting method:


- free-standing
- to screw


DESCRIPTION

Soft armchair is a single-seat armchair with armrests, lacking a backrest. It's anchored with wall plugs onto a solid surface like stone or concrete. This design caters to the needs of furniture ideal for senior citizens. A flat seat paired with tall armrests simplifies the actions of sitting down and standing up for the elderly or those with mobility challenges. This chair comes in various colors and materials. The more economical model is constructed from carbon steel, galvanized and powder-coated in any RAL color, while the seating surface is crafted from varnished spruce or pine. The premium version features a stainless-steel frame and your choice of exotic woods like sapeli, iroko, or meranti, finished with oil. This blend of materials not only offers an upscale look but also enhances the durability of the chair, boosting its resistance to external elements. The use of stainless steel and exotic woods ensures the chair maintains its pristine condition for an extended period. Additionally, its upkeep and cleaning are more...

SEAT SOFT 02.112.1 ZANO URBAN FURNITURE







GENERAL TECHNICAL DATA

Dimensions:

- width: 23 ¹/₄ in - length: 26 in

- seat height: 18 ¹/₂ in

- height of armrests: 27 1/4 in

Materials:

- wood: European coniferous or exotic

- steel: carbon or stainless

ZANO



Product: Seat Soft
Catalog number: 02.112.1

Twoma Zacust Designer: Iwona Żaczek

In accordance with the Polish Law on Copyright and Related Rights of 04.02.1994 (Official Journal of Laws No. 24, item 83, corrected: Journal of Laws No. 43, item 170) and in accordance with the EU copyright legislation including all EU directives and regulations on copyright, Zano Mirosław Zarotynski Company, reserves the copyright of drawings, descriptions, 3D models, renderings, graphics, content contained in offers, attachments to offers and all other documents. Its content is the intellectual property of ZANO Miroslaw Zarotinski company. The use of author's ideas, solutions, copying, distribution of photos, graphics or fragments of graphics, descriptive texts, for profit, without the permission of the author - ZANO Mirosław Zarotynski company - is prohibited and constitutes a copyright infringement and is punishable.

NOTE: The drawings do not reflect the actual dimensions of the foundation. These are only sample installation diagrams taking into account the type of anchoring and the material of the substrate to which to attach the furniture.

The size of the foundation depends on local foundation conditions.









INSTALLATION TO PAVING WITH FOUNDATION

Installation description

- 1. ZANO product
- 2. Quick-attachment / quickattachment or chemical anchor
- **3.** Stone paving / concrete paving / stone slabs / concrete slabs
- **4.** Sand ballast (approximately 2 4 cm)
- 5. Stone aggregate substructure
- **6.** Concrete foundation of C16/20 class (top surface of concrete 10 cm below paving surface)
- 7. Local land

MOUNTING TO PAVING

Installation description

- 1. ZANO product
- Quick-attachment / quickattachment or chemical anchor
- 3. Stone paving / concrete paving / stone slabs / concrete slabs
- **4.** Sand ballast (approximately 2 4 cm)
- 5. Stone aggregate substructure
- 6. Local land

MOUNTING TO CONCRETE / ASPHALT

Installation description

- 1. ZANO product
- Quick-attachment / quickattachment or chemical anchor
- **3.** Fixed restrained surface, such as concrete or asphalt
- 4. Concrete foundation of C16/20 class (top surface of concrete 10 cm below paving surface)
- 5. Stone aggregate substructure
- Sand ballast (approximately 2 4 cm)
- 7. Local land

MOUNTING TO CONCRETE FOUNDATION

Installation description

- 1. ZANO product
- 2. Quick-attachment / quickattachment or chemical anchor
- 3. Concrete foundation of C16/20 class (top surface of concrete 10 cm below paying surface)
- 4. Local land