POST CLIVO 01.072 ZANO URBAN FURNITURE









## **OPTIONS**

### **Construction:**

o stainless steel (Aisi 304)

## Mounting method:

- to be grouted in
- to screw


### Fence mounts:

- one-sided
- double-sided
- o no

## **DESCRIPTION**

Model 01.072 is a post crafted from satin-finished stainless steel. Its sleek and practical design features a unique angled top that adds a distinctive touch. This post can be installed using ground anchors or by setting it in concrete. With its contemporary look, the post serves as an innovative element for traffic management in modern city environments.

POST CLIVO 01.072 ZANO URBAN FURNITURE



## **GENERAL TECHNICAL DATA**

### **Dimensions:**

- height from ground surface: 39 1/4 in
- height with anchor section: 55 in

#### Materials:


- steel tube


### ZANO


In accordance with the Polish Law on Copyright and Related Rights of 04.02.1994 (Offcial Journal of Laws No. 24, item 83, corrected: Journal of Laws No. 43, item 170) and in accordance with the EU copyright legislation including all EU directives and regulations on copyright, Zano Mirosław Zarotynski Company, reserves the copyright of drawings, descriptions, 3D models, renderings, graphics, content contained in offers, attachments to offers and all other documents. Its content is the intellectual property of ZANO Miroslaw Zarotinski company. The use of author's ideas, solutions, copying, distribution of photos, graphics or fragments of graphics, descriptive texts, for profit, without the permission of the author - ZANO Mirosław Zarotynski company - is prohibited and constitutes a copyright infringement and is punishable.

NOTE: The drawings do not reflect the actual dimensions of the foundation. These are only sample installation diagrams taking into account the type of anchoring and the material of the substrate to which to attach the furniture.

The size of the foundation depends on local foundation conditions.







# INSTALLATION TO PAVING WITH FOUNDATION

### Installation description

- 1. ZANO product
- 2. Stone paving / concrete paving / stone slabs / concrete slabs
- 3. Sand ballast (approximately 2 4 cm)
- Concrete foundation of C16/20 class (top surface of concrete 10 cm below paving surface)
- 5. Local land

# MOUNTING TO CONCRETE FOUNDATION

### Installation description

- 1. ZANO product
- Concrete foundation of C16/20 class (top surface of concrete 10 cm below paving surface)
- 3. Local land


# MOUNTING TO CONCRETE FOUNDATION

### Installation description


- 1. ZANO product
- **2.** Fixed restrained surface, such as concrete or asphalt
- 3. Concrete foundation of C16/20 class (top surface of concrete 10 cm below paving surface)
- 4. Stone aggregate substructure
- Sand ballast (approximately 2 4 cm)
- 6. Local land


NOTE: The drawings do not reflect the actual dimensions of the foundation. These are only sample installation diagrams taking into account the type of anchoring and the material of the substrate to which to attach the furniture.

The size of the foundation depends on local foundation conditions.









# INSTALLATION TO PAVING WITH FOUNDATION

#### Installation description

- 1. ZANO product
- Quick-attachment / quickattachment or chemical anchor
- **3.** Stone paving / concrete paving / stone slabs / concrete slabs
- **4.** Sand ballast (approximately 2 4 cm)
- 5. Stone aggregate substructure
- **6.** Concrete foundation of C16/20 class (top surface of concrete 10 cm below paving surface)
- 7. Local land

### **MOUNTING TO PAVING**

#### Installation description

- 1. ZANO product
- 2. Quick-attachment / quickattachment or chemical anchor
- 3. Stone paving / concrete paving / stone slabs / concrete slabs
- **4.** Sand ballast (approximately 2 4 cm)
- 5. Stone aggregate substructure
- 6. Local land

# MOUNTING TO CONCRETE / ASPHALT

### Installation description

- 1. ZANO product
- Quick-attachment / quickattachment or chemical anchor
- **3.** Fixed restrained surface, such as concrete or asphalt
- 4. Concrete foundation of C16/20 class (top surface of concrete 10 cm below paving surface)
- 5. Stone aggregate substructure
- Sand ballast (approximately 2 4 cm)
- 7. Local land

# MOUNTING TO CONCRETE FOUNDATION

#### Installation description

- 1. ZANO product
- 2. Quick-attachment / quickattachment or chemical anchor
- 3. Concrete foundation of C16/20 class (top surface of concrete 10 cm below paying surface)
- 4. Local land