



OPTIONS

Construction:

• carbon steel (s235Jr)

Mounting method:

• to be grouted in

Ears for chain attachment:

- ∘ no
- attachment of 1 chain (both sides)
- attachment of 1 chain (end)
- attachment of 2 chains (both sides)
- attachment of 2 chains (final)


Fence mounts:

- one-sided
- double-sided
- no

DESCRIPTION

The traditional style of the Tempo post allows it to fit perfectly in any setting, looking sharp in both historic areas and contemporary residential developments.

The post is secured by embedding it in concrete, which prevents it from being pulled out or damaged by vandals. These posts can be utilized to safeguard roads, sidewalks, or pathways. They are offered in three models: earless, with two ears for hanging chains, and with four ears for hanging chains.



GENERAL TECHNICAL DATA

Dimensions:

- height from ground surface: 35 ¹/₂ in
- height with anchor section: 49 $1/_4$ in

Materials:

- cast iron
- steel tube: 50 mm





Product: Tempo post Catalog number: **01.052** WHQ / Designer: Tomasz Szpytma


In accordance with the Polish Law on Copyright and Related Rights of 04.02.1994 (Offcial Journal of Laws No. 24, item 83, corrected: Journal of Laws No. 43, item 170) and in accordance with the EU copyright legislation including all EU directives and regulations on copyright, Zano Mirosław Zarotynski Company, reserves the copyright of drawings, descriptions, 3D models, renderings, graphics, content contained in offers, attachments to offers and all other documents. Its content is the intellectual property of ZANO Miroslaw Zarotinski company. The use of author's ideas, solutions, copying, distribution of photos, graphics or fragments of graphics, descriptive texts, for profit, without the permission of the author - ZANO Miroslaw Zarotynski company - is prohibited and constitutes a copyright infringement and is punishable.

MOUNTING DIAGRAMS (E, F, G) FOR MOUNTING TO THE FOUNDATION

NOTE: The drawings do not reflect the actual dimensions of the foundation. These are only sample installation diagrams taking into account the type of anchoring and the material of the substrate to which to attach the furniture.

G


The size of the foundation depends on local foundation conditions.



INSTALLATION TO PAVING WITH FOUNDATION

Installation description


- 1. ZANO product
- 2. Stone paving / concrete paving / stone slabs / concrete slabs
- 3. Sand ballast (approximately 2 4 cm)
- 4. Concrete foundation of C16/20 class (top surface of concrete 10 cm below paving surface)
- 5. Local land



MOUNTING TO CONCRETE FOUNDATION

Installation description

- 1. ZANO product
- 2. Concrete foundation of C16/20 class (top surface of concrete 10 cm below paving surface)
- 3. Local land



MOUNTING TO CONCRETE FOUNDATION

Installation description

- 1. ZANO product
- 2. Fixed restrained surface, such as concrete or asphalt
- **3.** Concrete foundation of C16/20 class (top surface of concrete 10 cm below paving surface)
- 4. Stone aggregate substructure
- 5. Sand ballast (approximately 2 4 cm)
- 6. Local land