

OPTIONS

Construction:

- carbon steel (s235Jr)
- stainless steel (Aisi 304)

Seat:

- European coniferous wood
- hardwood of European origin
- oiled exotic wood
- premium exotic wood
- ecoplank

Mounting method:

- to screw

DESCRIPTION

The presented seat is a continuation of the popular Flash collection. This bench was designed for arranging and managing previously unused public spaces. The innovative design of the Flash seat makes it possible to create a modular bench on such components as walls, walls or low concrete fences. The Flash bench thus makes it possible to activate unattractive and often unexploited elements of urban space, creating instead an effective place for meetings, recreation and rest. The design of the Flash seat is based on a steel structure (optional stainless steel) and a wooden seat (made of domestic or exotic wood). Installation of the bench is done with the help of expansion bolts or anchors. It is also possible to concrete the entire structure. Flash design is intended for both indoor and outdoor spaces. However, for outdoor use, it should be remembered that wood as a natural material is subject to the influence of changing atmospheric factors, so it requires maintenance and care at least once a year. Flash bench will be a great...

GENERAL TECHNICAL DATA

Dimensions:

- width: 17 in
- length: 70 ³/₄ in
- height: 7 ³/₄ in

Weight:


- 44 lb

Materials:

- wood: European coniferous or exotic
- stainless or carbon steel

Comments:

- The concrete pedestal is not an integral part of the Flash Seat 02.725.





ZANO


M. Welmiński


Product: Bench Flash
 Catalog number: **02.725**
 Designer:
 Mateusz Welmiński

In accordance with the Polish Law on Copyright and Related Rights of 04.02.1994 (Official Journal of Laws No. 24, item 83, corrected: Journal of Laws No. 43, item 170) and in accordance with the EU copyright legislation including all EU directives and regulations on copyright, Zano Mirosław Zarotynski Company, reserves the copyright of drawings, descriptions, 3D models, renderings, graphics, content contained in offers, attachments to offers and all other documents. Its content is the intellectual property of ZANO Mirosław Zarotynski company. The use of author's ideas, solutions, copying, distribution of photos, graphics or fragments of graphics, descriptive texts, for profit, without the permission of the author - ZANO Mirosław Zarotynski company - is prohibited and constitutes a copyright infringement and is punishable.



NOTE: The drawings do not reflect the actual dimensions of the foundation. These are only sample installation diagrams taking into account the type of anchoring and the material of the substrate to which to attach the furniture.


The size of the foundation depends on local foundation conditions.



INSTALLATION TO PAVING WITH FOUNDATION

Installation description


1. ZANO product
2. Quick-attachment / quick-attachment or chemical anchor
3. Stone paving / concrete paving / stone slabs / concrete slabs
4. Sand ballast (approximately 2 - 4 cm)
5. Stone aggregate substructure
6. Concrete foundation of C16/20 class (top surface of concrete 10 cm below paving surface)
7. Local land



MOUNTING TO PAVING

Installation description


1. ZANO product
2. Quick-attachment / quick-attachment or chemical anchor
3. Stone paving / concrete paving / stone slabs / concrete slabs
4. Sand ballast (approximately 2 - 4 cm)
5. Stone aggregate substructure
6. Local land



MOUNTING TO CONCRETE / ASPHALT

Installation description

1. ZANO product
2. Quick-attachment / quick-attachment or chemical anchor
3. Fixed restrained surface, such as concrete or asphalt
4. Concrete foundation of C16/20 class (top surface of concrete 10 cm below paving surface)
5. Stone aggregate substructure
6. Sand ballast (approximately 2 - 4 cm)
7. Local land



MOUNTING TO CONCRETE FOUNDATION

Installation description

1. ZANO product
2. Quick-attachment / quick-attachment or chemical anchor
3. Concrete foundation of C16/20 class (top surface of concrete 10 cm below paving surface)
4. Local land