



OPTIONS

Construction:

- carbon steel (s235Jr)
- stainless steel (Aisi 304)

Housing:

- European coniferous wood
- hardwood of European origin
- oiled exotic wood
- premium exotic wood
- concrete
- HPL board

Mounting method:

• to screw

Ashtray:

• with an ashtray

Contribution:

• galvanized sheet insert

DESCRIPTION

The Altus four-compartment recycling bin is designed for sorting waste and combines aesthetic steel with premium wood in its construction. Customers can choose between structural steel coated with RAL paint or stainless steel, paired with either domestic or exotic wood finishes. This model features four sections, each equipped with a galvanized liner. For waste separation, users can either use just the liner or add disposable bags in designated recycling colors. The Altus bin is exceptionally practical, with each wooden slat featuring engraved labels that indicate the intended use of each compartment. Customization is available, allowing for the alteration of these labels according to customer preferences. The Altus recycling station can operate as a...

GENERAL TECHNICAL DATA

Dimensions:

- width: 15 in
- height: 32 1/4 in

Capacity:

- capacity: 14 1/2 gal

Materials:

- stainless steel profiles
- galvanized sheet insert
- wooden planks

ZANO


In accordance with the Polish Law on Copyright and Related Rights of 04.02.1994 (Offcial Journal of Laws No. 24, item 83, corrected: Journal of Laws No. 43, item 170) and in accordance with the EU copyright legislation including all EU directives and regulations on copyright , Zano Mirosław Zarotynski Company, reserves the copyright of drawings, descriptions, 3D models, renderings, graphics, content contained in offers, attachments to offers and all other documents. Its content is the intellectual property of ZANO Miroslaw Zarotinski company. The use of author's ideas, solutions, copying, distribution of photos, graphics or fragments of graphics, descriptive texts, for profit, without the permission of the author - ZANO Miroslaw Zarotynski company - is prohibited and constitutes a copyright infringement and is punishable.





NOTE: The drawings do not reflect the actual dimensions of the foundation. These are only sample installation diagrams taking into account the type of anchoring and the material of the substrate to which to attach the furniture.

The size of the foundation depends on local foundation conditions.









INSTALLATION TO PAVING WITH FOUNDATION

Installation description

- 1. ZANO product
- 2. Quick-attachment / quickattachment or chemical anchor
- 3. Stone paving / concrete paving / stone slabs / concrete slabs
- 4. Sand ballast (approximately 2 4 cm)
- **5.** Stone aggregate substructure
- 6. Concrete foundation of C16/20 class (top surface of concrete 10 cm below paving surface)
- 7. Local land

MOUNTING TO PAVING

Installation description

- 1. ZANO product
- 2. Quick-attachment / quickattachment or chemical anchor
- 3. Stone paving / concrete paving / stone slabs / concrete slabs
- Sand ballast (approximately 2 4 cm)
- 5. Stone aggregate substructure
- 6. Local land

MOUNTING TO CONCRETE / ASPHALT

Installation description

- 1. ZANO product
- 2. Quick-attachment / quickattachment or chemical anchor
- **3.** Fixed restrained surface, such as concrete or asphalt
- Concrete foundation of C16/20 class (top surface of concrete 10 cm below paving surface)
- 5. Stone aggregate substructure
- 6. Sand ballast (approximately 2 4 cm)
- 7. Local land

MOUNTING TO CONCRETE FOUNDATION

Installation description

1. ZANO product

- 2. Quick-attachment / quickattachment or chemical anchor
- **3.** Concrete foundation of C16/20 class (top surface of concrete 10 cm below paving surface)
- 4. Local land