

OPTIONS

Construction:

• stainless steel (Aisi 304)

Mounting method:

- to be grouted in
- to screw

Fence mounts:

- one-sided
- double-sided
- ∘ no

DESCRIPTION

Contemporary Pila stainless steel post topped with a sphere, creating a unique appearance. A fusion of modern and classic styles.



GENERAL TECHNICAL DATA

Dimensions:

- height from ground surface: 39 $^{1}/_{4}$ in


- height with anchor section: 55 in

Materials:

- steel tube

ZANO

In accordance with the Polish Law on Copyright and Related Rights of 04.02.1994 (Offcial Journal of Laws No. 24, item 83, corrected: Journal of Laws No. 43, item 170) and in accordance with the EU copyright legislation including all EU directives and regulations on copyright, Zano Mirosław Zarotynski Company, reserves the copyright of drawings, descriptions, 3D models, renderings, graphics, content contained in offers, attachments to offers and all other documents. Its content is the intellectual property of ZANO Mirosław Zarotinski company. The use of author's ideas, solutions, copying, distribution of photos, graphics or fragments of graphics, descriptive texts, for profit, without the permission of the author - ZANO Mirosław Zarotynski company - is prohibited and constitutes a copyright infringement and is punishable.




MOUNTING DIAGRAMS (E, F, G) FOR MOUNTING TO THE FOUNDATION

NOTE: The drawings do not reflect the actual dimensions of the foundation. These are only sample installation diagrams taking into account the type of anchoring and the material of the substrate to which to attach the furniture.

G


The size of the foundation depends on local foundation conditions.



INSTALLATION TO PAVING WITH FOUNDATION

Installation description

- 1. ZANO product
- 2. Stone paving / concrete paving / stone slabs / concrete slabs
- 3. Sand ballast (approximately 2 4 cm)
- 4. Concrete foundation of C16/20 class (top surface of concrete 10 cm below paving surface)
- 5. Local land



MOUNTING TO CONCRETE FOUNDATION

Installation description

- 1. ZANO product
- 2. Concrete foundation of C16/20 class (top surface of concrete 10 cm below paving surface)
- 3. Local land



3

2


Installation description


- 1. ZANO product
- 2. Fixed restrained surface, such as concrete or asphalt
- **3.** Concrete foundation of C16/20 class (top surface of concrete 10 cm below paving surface)
- 4. Stone aggregate substructure
- 5. Sand ballast (approximately 2 4 cm)
- 6. Local land


NOTE: The drawings do not reflect the actual dimensions of the foundation. These are only sample installation diagrams taking into account the type of anchoring and the material of the substrate to which to attach the furniture.

The size of the foundation depends on local foundation conditions.









INSTALLATION TO PAVING WITH FOUNDATION

Installation description

- 1. ZANO product
- 2. Quick-attachment / quickattachment or chemical anchor
- 3. Stone paving / concrete paving / stone slabs / concrete slabs
- 4. Sand ballast (approximately 2 4 cm)
- **5.** Stone aggregate substructure
- 6. Concrete foundation of C16/20 class (top surface of concrete 10 cm below paving surface)
- 7. Local land

MOUNTING TO PAVING

Installation description

- 1. ZANO product
- 2. Quick-attachment / quickattachment or chemical anchor
- 3. Stone paving / concrete paving / stone slabs / concrete slabs
- Sand ballast (approximately 2 4 cm)
- 5. Stone aggregate substructure
- 6. Local land

MOUNTING TO CONCRETE / ASPHALT

Installation description

- 1. ZANO product
- 2. Quick-attachment / quickattachment or chemical anchor
- **3.** Fixed restrained surface, such as concrete or asphalt
- Concrete foundation of C16/20 class (top surface of concrete 10 cm below paving surface)
- 5. Stone aggregate substructure
- 6. Sand ballast (approximately 2 4 cm)
- 7. Local land

MOUNTING TO CONCRETE FOUNDATION

Installation description

1. ZANO product

- 2. Quick-attachment / quickattachment or chemical anchor
- **3.** Concrete foundation of C16/20 class (top surface of concrete 10 cm below paving surface)
- 4. Local land