




OPTIONS

Construction:

- carbon steel (s235Jr)

Mounting method:

- to be grouted in


Number of parking spaces:

- space for 6 bicycles
- spaces for 8 bicycles
- spaces for 10 bicycles
- spaces for 12 bicycles
- spaces for 14 bicycles

DESCRIPTION

The stand is produced in two styles: either polished stainless steel or "black" steel, which can be painted in any RAL color. The design of the stand is highly user-oriented. The Fractal 05.425 bike stand seamlessly integrates into any setting, looking equally fantastic whether placed in a contemporary downtown area or an old historic district.





GENERAL TECHNICAL DATA

Dimensions:

- width: 31 1/2 in
- length: 78 3/4 in
- height from ground surface: 31 1/2 in
- height with anchor section: 55 in

Materials:


- steel tubes
- closed profiles

ZANO

In accordance with the Polish Law on Copyright and Related Rights of 04.02.1994 (Official Journal of Laws No. 24, item 83, corrected: Journal of Laws No. 43, item 170) and in accordance with the EU copyright legislation including all EU directives and regulations on copyright, Zano Mirosław Zarotynski Company, reserves the copyright of drawings, descriptions, 3D models, renderings, graphics, content contained in offers, attachments to offers and all other documents. Its content is the intellectual property of ZANO Mirosław Zarotynski company. The use of author's ideas, solutions, copying, distribution of photos, graphics or fragments of graphics, descriptive texts, for profit, without the permission of the author - ZANO Mirosław Zarotynski company - is prohibited and constitutes a copyright infringement and is punishable.

NOTE: The drawings do not reflect the actual dimensions of the foundation. These are only sample installation diagrams taking into account the type of anchoring and the material of the substrate to which to attach the furniture.


The size of the foundation depends on local foundation conditions.



INSTALLATION TO PAVING WITH FOUNDATION

Installation description


1. ZANO product
2. Stone paving / concrete paving / stone slabs / concrete slabs
3. Sand ballast (approximately 2 - 4 cm)
4. Concrete foundation of C16/20 class (top surface of concrete 10 cm below paving surface)
5. Local land



MOUNTING TO CONCRETE FOUNDATION

Installation description

1. ZANO product
2. Concrete foundation of C16/20 class (top surface of concrete 10 cm below paving surface)
3. Local land



MOUNTING TO CONCRETE FOUNDATION

Installation description

1. ZANO product
2. Fixed restrained surface, such as concrete or asphalt
3. Concrete foundation of C16/20 class (top surface of concrete 10 cm below paving surface)
4. Stone aggregate substructure
5. Sand ballast (approximately 2 - 4 cm)
6. Local land