

OPTIONS

Construction:

- carbon steel (s235Jr)

Mounting method:


- to be grouted in


Fence mounts:

- one-sided
- double-sided
- no

DESCRIPTION

Solo fence post constructed from black steel, featuring a tape (flat bar). It serves multiple purposes, including dividing green zones from pedestrian paths and streets. The Solo 01.053 model consists of steel tubing and boasts a cast iron finish with a stylized appearance. The post's traditional design ensures it fits seamlessly into both vintage and contemporary settings. Installation of the featured post is achieved by embedding it in concrete.





GENERAL TECHNICAL DATA

Dimensions:

- height from ground surface: 21 ³/₄ in
- height with anchor section: 39 ¹/₄ in
- maximum strap length: 98 ¹/₂ in

Materials:

- cast iron
- steel tube: 50 mm
- steel flat bar 45x8mm

ZANO



Product: Post Solo
 Catalog number: **01.053**
 Designer: Tomasz Szpytma

In accordance with the Polish Law on Copyright and Related Rights of 04.02.1994 (Official Journal of Laws No. 24, item 83, corrected: Journal of Laws No. 43, item 170) and in accordance with the EU copyright legislation including all EU directives and regulations on copyright, Zano Mirosław Zarotynski Company, reserves the copyright of drawings, descriptions, 3D models, renderings, graphics, content contained in offers, attachments to offers and all other documents. Its content is the intellectual property of ZANO Mirosław Zarotynski company. The use of author's ideas, solutions, copying, distribution of photos, graphics or fragments of graphics, descriptive texts, for profit, without the permission of the author - ZANO Mirosław Zarotynski company - is prohibited and constitutes a copyright infringement and is punishable.

NOTE: The drawings do not reflect the actual dimensions of the foundation. These are only sample installation diagrams taking into account the type of anchoring and the material of the substrate to which to attach the furniture.

The size of the foundation depends on local foundation conditions.



INSTALLATION TO PAVING WITH FOUNDATION

Installation description

1. ZANO product
2. Stone paving / concrete paving / stone slabs / concrete slabs
3. Sand ballast (approximately 2 - 4 cm)
4. Concrete foundation of C16/20 class (top surface of concrete 10 cm below paving surface)
5. Local land



MOUNTING TO CONCRETE FOUNDATION

Installation description

1. ZANO product
2. Concrete foundation of C16/20 class (top surface of concrete 10 cm below paving surface)
3. Local land



MOUNTING TO CONCRETE FOUNDATION

Installation description

1. ZANO product
2. Fixed restrained surface, such as concrete or asphalt
3. Concrete foundation of C16/20 class (top surface of concrete 10 cm below paving surface)
4. Stone aggregate substructure
5. Sand ballast (approximately 2 - 4 cm)
6. Local land