



## OPTIONS

### Construction:

- carbon steel (s235Jr)
- stainless steel (Aisi 304)

### Seat and backrest:

- European coniferous wood
- hardwood of European origin
- oiled exotic wood
- premium exotic wood
- HPL board



### Mounting method:

- to screw

## DESCRIPTION

The Scandik 02.046.1 Bench epitomizes the sleek, functional aesthetics of Scandinavian urban furniture. It's all about minimalist design, clean lines, and meticulous attention to detail, making the bench both modern and visually appealing. This piece is superb for contemporary environments and is highly recommended for outdoor settings like parks, urban streets, and plazas. The Scandik 02.046.1 model includes both a backrest and armrests, offering additional comfort, particularly beneficial for elderly users. There are also models available only with a backrest or without any backrest at all.

The bench's framework is crafted from steel, with options in stainless steel or carbon steel, which can be galvanized and powder-coated in any desired RAL color. The seating surface and backrest finishes come in wood, with alternatives in either HPL laminate or steel. Wooden options include local or exotic varieties. To ensure stability, the whole bench is anchored to the ground using dowels.



## GENERAL TECHNICAL DATA

### Dimensions:

- width: 60 <sup>3</sup>/<sub>4</sub> in
- depth: 20 <sup>1</sup>/<sub>4</sub> in
- seat height: 17 <sup>1</sup>/<sub>4</sub> in
- height with backrest: 32 in

### Weight:

- 132 lb

### Materials:

- steel: carbon or stainless
- domestic coniferous or exotic wood (iroko, sapeli, meranti, tauari)
- HPL

ZANO


*Iwona Żaczek*

Product: Scandik bench  
 Catalog number: **02.046.1**  
 Designer: Iwona Żaczek

In accordance with the Polish Law on Copyright and Related Rights of 04.02.1994 (Official Journal of Laws No. 24, item 83, corrected: Journal of Laws No. 43, item 170) and in accordance with the EU copyright legislation including all EU directives and regulations on copyright, Zano Miroslaw Zarotynski Company, reserves the copyright of drawings, descriptions, 3D models, renderings, graphics, content contained in offers, attachments to offers and all other documents. Its content is the intellectual property of ZANO Miroslaw Zarotynski company. The use of author's ideas, solutions, copying, distribution of photos, graphics or fragments of graphics, descriptive texts, for profit, without the permission of the author - ZANO Miroslaw Zarotynski company - is prohibited and constitutes a copyright infringement and is punishable.

**NOTE:** The drawings do not reflect the actual dimensions of the foundation. These are only sample installation diagrams taking into account the type of anchoring and the material of the substrate to which to attach the furniture.

The size of the foundation depends on local foundation conditions.



### INSTALLATION TO PAVING WITH FOUNDATION

#### Installation description

1. ZANO product
2. Quick-attachment / quick-attachment or chemical anchor
3. Stone paving / concrete paving / stone slabs / concrete slabs
4. Sand ballast (approximately 2 - 4 cm)
5. Stone aggregate substructure
6. Concrete foundation of C16/20 class (top surface of concrete 10 cm below paving surface)
7. Local land



### MOUNTING TO PAVING

#### Installation description

1. ZANO product
2. Quick-attachment / quick-attachment or chemical anchor
3. Stone paving / concrete paving / stone slabs / concrete slabs
4. Sand ballast (approximately 2 - 4 cm)
5. Stone aggregate substructure
6. Local land



### MOUNTING TO CONCRETE / ASPHALT

#### Installation description

1. ZANO product
2. Quick-attachment / quick-attachment or chemical anchor
3. Fixed restrained surface, such as concrete or asphalt
4. Concrete foundation of C16/20 class (top surface of concrete 10 cm below paving surface)
5. Stone aggregate substructure
6. Sand ballast (approximately 2 - 4 cm)
7. Local land



### MOUNTING TO CONCRETE FOUNDATION

#### Installation description

1. ZANO product
2. Quick-attachment / quick-attachment or chemical anchor
3. Concrete foundation of C16/20 class (top surface of concrete 10 cm below paving surface)
4. Local land